


ACE TrackRunner Self Driver

Remote Head	
Camera	Any first line production camera
Lens	Canon, Sony, Fujinon
Max Payload (Remote head + Camera)	175 lbs
Remote Head	Nettmann Stab-C, Stab-C Compact, Mini-C, MiniMote SAS
Lens Height (From floor / support)	Dependent of Remote Head - Mini-C = 32", Stab-C Compact = 34"
Track Sizes	
Straight High Speed Track	2m (6.6') Sections - Silver
Straight ENT Track	2m (6.6') Sections - Black
Curved ENT Track - 20 Degrees/section	37' Diameter Circle (116' Circumference) - Black
Width for safe clearance of track	14"
Width for safe clearance of camera and head	42"
Track Speeds	
Max Speed - With Energy Chain (Cable Management)	6.5 m/s - 14.5 mph (21.3 feet per second)
Max Accesleration - With Energy Chain (Cable Management)	Fully adjustable speed ramps
Track Control	
Operator Options	Joystick, pedals, computer, touchscreen
Dimensions (inches) & Weights (Lbs)	
Dolly - LxWxH	71"x 15"x 14" - 95 lbs
Straight Track - LxWxH	79"x 12"x 7.87 - 10.24" - 43 lbs / section
20° Curve Track	83"x 16.5"x 7.87 - 10.24" - 50 lbs / section
Track Power and Cabling	
Power Requirements	120V AC (20 AMP) with use of ACE 2K Transfomer
Built in Cable Management	Pre-built or assembled to production needs (Fiber, Paint, etc)
Shipping Weights and Sizes	
Gross Weight - TrackRunner	Depends on Track Needs
Straight ENT Track (2m sections)	83x42x33 / 600 lbs
Curve ENT Track (20 Degree sections) Case	90x39x45 / 700 lbs
TrackRunner Self Driver Case	83x42x33 / 600 lbs



WWW.ACEEAST.COM