

Dollies
Peds &
Heads

Booms & bases

Home

Model 11 Dolly

Model 10 Dolly

Model 9 Dolly


Spyder Dolly

Jib Arm Dolly

Quattro Pedestal

Vector Head

Model 10 Dolly



General Description

Features

Specifications

Dimensioned Drawings

Standard Accessories

Optional Accessories

Track

Awards

Technical Bulletins

Specifications

Max. lift beam elevation with Standard Level Head (SLT)	62.625 inches(159.068 cm)
Min. lift beam elevation with Standard Level Head (SLT)	13.75 inches (34.925 cm)
Min. lift beam elevation with Low Level Head (LHT)	3.125 inches (7.938 cm)
Vertical beam travel	46.875 inches (119.063 cm)
Lift capacity	500 pounds (226.8 kg)
Length	55.5 inches (140.97 cm)
Width	26.5 inches (67.31 cm)
Height (operating)	38.625 inches (98.108 cm)
Height (folded)	25 inches (63.5 cm)
Minimum turn radius (round steering)	22 inches (55.88 cm)
Minimum turn radius (conventional steering)	44 inches (111.76 cm)
Carrying weight	420 pounds (190.51 kg)
Maximum Dolly load capacity	900 pounds (408.23 kg)
Lifts per system charge	7